

# MICRO-FRAISE Z2 · MICRO-ENDMILL Z2 · MICRO-FRÄSER Z2



21032A-0.9

Version 07.05.2026

SWISS MADE

|   |  |  |   |   |                                     |
|---|--|--|---|---|-------------------------------------|
| <p>E25 UF</p> <p>CARBIDE TOOL MATERIAL E25 UF</p> | <p><math>\lambda = 35^\circ</math><br/><math>\gamma = 10^\circ</math></p> <p>CUTTING ANGLES <math>\gamma 35^\circ \gamma 10^\circ</math></p> | <p>angle vif</p> <p>ACUTE ANGLE PRECISION TOOL</p> | <p>DUAL DIRECTION HELICAL DRILL BIT</p> | <p>2.2xD</p> <p>2.2xD DEPTH FOR TOOLS</p> | <p>TOOL LENGTH MEASUREMENT BARS</p> |
|---|--|--|---|---|-------------------------------------|

## MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

| MATERIAL  | SPECIFICATION                | GRP | 21032A-0.9 |
|---|------------------------------|-----|------------|
| <b>Alloyed and non-alloyed steels</b><br>Non-alloyed steels | Rm < 450 N/mm <sup>2</sup>   | 1a  | ●●○        |
|   | Rm 450–700 N/mm <sup>2</sup> | 1b  | ●●○        |
|   | Rm 700–900 N/mm <sup>2</sup> | 1c  | ●●○        |
|   | Rm > 1200 N/mm <sup>2</sup>  | 1d  | ●○○        |
| <b>Stainless steels</b><br>Stainless steels                 | Rm < 650 N/mm <sup>2</sup>   | 2a  | ●●○        |
|   | Rm 650–950 N/mm <sup>2</sup> | 2b  | ●●○        |
|   | Rm > 950 N/mm <sup>2</sup>   | 2c  | ●○○        |
| <b>Hardened steels</b><br>Hardened steels                   | 44–56 HRC                    | 3a  | ○○○        |
|   | 57–67 HRC                    | 3b  | ○○○        |
| <b>Exotic materials</b><br>Special alloys                   | < 32 HRC                     | 4a  | ●○○        |
|   | > 32 HRC                     | 4b  | ●○○        |
| <b>Graphite</b><br>Industrial graphite                      |                              | 5   | ●●○        |
| <b>Cast iron</b><br>Grey / nodular cast iron                | < 32 HRC                     | 6a  | ●●○        |
|   | > 32 HRC                     | 6b  | ●●○        |
| <b>Titanium</b><br>Titanium alloys                          | Rm < 600 N/mm <sup>2</sup>   | 7a  | ●●○        |
|   | 600 < Rm N/mm <sup>2</sup>   | 7b  | ●●○        |
| <b>Nickel alloys</b><br>Inconel, Hastelloy                  | Rm < 1000 N/mm <sup>2</sup>  | 8a  | ●○○        |
|   | Rm > 1000 N/mm <sup>2</sup>  | 8b  | ●○○        |
| <b>Copper, brass, bronze</b><br>Copper-based                | Rm < 850 N/mm <sup>2</sup>   | 9a  | ●●○        |
|   | Rm > 850 N/mm <sup>2</sup>   | 9b  | ●●○        |
| <b>Aluminum</b><br>Aluminum alloys                          | Si < 0.5%                    | 10a | ●○○        |
|   | 0.5% < Si < 5%               | 10b | ●○○        |
|   | Si > 5%                      | 10c | ●○○        |
| <b>Synthetic materials</b><br>Engineering plastics          | Thermoplastic                | 11a | ○○○        |
|   | Thermoset                    | 11b | ○○○        |
| <b>Composite materials</b><br>Reinforced composites         | Glass fiber / GFK            | 12a | ●●○        |
|   | Carbon fiber / KFK           | 12b | ●●○        |
| <b>Precious metals</b><br>Gold, platinum, silver            | Gold                         | 13a | ●○○        |
|   | Platinum                     | 13b | ●○○        |

## TECHNICAL DRAWING



## DIMENSIONS

| NOMINAL DIMENSIONS |        |
|--------------------|--------|
| D (0 / -0.01)      | 0.9 mm |
| d (h5)             | 3 mm   |
| L                  | 38 mm  |
| l1                 | 2.7 mm |
| l3                 | –      |
| d3                 | –      |
| R                  | –      |
| e                  | –      |
| Z                  | 2      |
| Chamfer K          | –      |
| w° collision       | 8.6°   |



E-SHOP / EZI CUT  
eskenazi.ch/eshop/21032A-0.9

© 2026 Eskenazi SA — Carouge, Genève  
All rights reserved