


# MICRO-FRAISE Z3 · MICRO-ENDMILL Z3 · MICRO-FRÄSER Z3



21036D-0.8

Version 06.05.2026




|   |  |  |   |  |                                    |                              |                                 |
|---|--|--|---|--|------------------------------------|------------------------------|---------------------------------|
| <p>E25 UF</p> <p>CARBIDE TOOL MATERIAL E25 UF</p> | <p><math>\lambda=30^{\circ}-35^{\circ}</math><br/><math>\gamma=8^{\circ}</math></p> <p>CUTTING ANGLES<br/><math>730^{\circ}-35^{\circ} 78^{\circ}</math></p> | <p>angle vif</p> <p>ACUTE ANGLE PRECISION TOOL</p> | <p>DUAL DIRECTION HELICAL DRILL BIT</p> | <p>1.5xD</p> <p>1.5XD DEPTH PRECISION TOOL</p> | <p>SHORT LENGTH TOOL WEAR BARS</p> | <p>ADJUSTABLE ANGLE ICON</p> | <p>VARIABLE HELIX DRILL BIT</p> |
|---|--|--|---|--|------------------------------------|------------------------------|---------------------------------|

## MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●● Good (2/3) ●○ Possible (1/3) ○○○ Not recommended

| MATERIAL   | SPECIFICATION                | GRP | 21036D-0.8 |
|--|------------------------------|-----|------------|
| <b>Alloyed and non-alloyed steels</b><br><small>Non-alloyed steels</small> | Rm < 450 N/mm <sup>2</sup>   | 1a  | ○○○        |
|  | Rm 450–700 N/mm <sup>2</sup> | 1b  | ○○○        |
|  | Rm 700–900 N/mm <sup>2</sup> | 1c  | ○○○        |
|  | Rm > 1200 N/mm <sup>2</sup>  | 1d  | ○○○        |
| <b>Stainless steels</b><br><small>Stainless steels</small>                 | Rm < 650 N/mm <sup>2</sup>   | 2a  | ○○○        |
|  | Rm 650–950 N/mm <sup>2</sup> | 2b  | ○○○        |
|  | Rm > 950 N/mm <sup>2</sup>   | 2c  | ○○○        |
| <b>Hardened steels</b><br><small>Hardened steels</small>                   | 44–56 HRC                    | 3a  | ○○○        |
|  | 57–67 HRC                    | 3b  | ○○○        |
| <b>Exotic materials</b><br><small>Special alloys</small>                   | < 32 HRC                     | 4a  | ○○○        |
|  | > 32 HRC                     | 4b  | ○○○        |
| <b>Graphite</b><br><small>Industrial graphite</small>                      |                              | 5   | ●●●        |
| <b>Cast iron</b><br><small>Grey / nodular cast iron</small>                | < 32 HRC                     | 6a  | ○○○        |
|  | > 32 HRC                     | 6b  | ○○○        |
| <b>Titanium</b><br><small>Titanium alloys</small>                          | Rm < 600 N/mm <sup>2</sup>   | 7a  | ○○○        |
|  | 600 < Rm N/mm <sup>2</sup>   | 7b  | ○○○        |
| <b>Nickel alloys</b><br><small>Inconel, Hastelloy</small>                  | Rm < 1000 N/mm <sup>2</sup>  | 8a  | ○○○        |
|  | Rm > 1000 N/mm <sup>2</sup>  | 8b  | ○○○        |
| <b>Copper, brass, bronze</b><br><small>Copper-based</small>                | Rm < 850 N/mm <sup>2</sup>   | 9a  | ●●○        |
|  | Rm > 850 N/mm <sup>2</sup>   | 9b  | ●●○        |
| <b>Aluminum</b><br><small>Aluminum alloys</small>                          | Si < 0.5%                    | 10a | ●○●        |
|  | 0.5% < Si < 5%               | 10b | ●●○        |
|  | Si > 5%                      | 10c | ●●●        |
| <b>Synthetic materials</b><br><small>Engineering plastics</small>          | Thermoplastic                | 11a | ○○○        |
|  | Thermoset                    | 11b | ○○○        |
| <b>Composite materials</b><br><small>Reinforced composites</small>         | Glass fiber / GFK            | 12a | ●●●        |
|  | Carbon fiber / KFK           | 12b | ●●●        |
| <b>Precious metals</b><br><small>Gold, platinum, silver</small>            | Gold                         | 13a | ●●○        |
|  | Platinum                     | 13b | ●●●        |

## TECHNICAL DRAWING



## DIMENSIONS

| NOMINAL DIMENSIONS |        |
|--------------------|--------|
| D (0 / -0.01)      | 0.8 mm |
| d (h5)             | 3 mm   |
| L                  | 38 mm  |
| l1                 | 1 mm   |
| l3                 | –      |
| d3                 | –      |
| R                  | –      |
| e                  | –      |
| Z                  | 3      |
| Chamfer K          | –      |
| w° collision       | 11.1°  |



E-SHOP / EZI CUT  
eskenazi.ch/eshop/21036D-0.8

© 2026 Eskenazi SA — Carouge, Genève  
All rights reserved