

E2 E2 HIGH PRECISION TOOL MATERIAL	$\lambda=30^{\circ}\text{-}35^{\circ}$ $\gamma=8^{\circ}$ CUTTING ANGLES $730^{\circ}\text{-}35^{\circ}$ 78°	$0 \leq \phi \leq 6$ 90° 45° CHAMFER $\phi < 6$ $\phi > 6$ 90° 45°	DUAL DIRECTION HELICAL DRILL BIT	h_1 1.5xD 1.5XD DEPTH PRECISION TOOL	SHORT LENGTH TOOL WEAR BARS	ADJUSTABLE ANGLE ICON	VARIABLE HELIX DRILL BIT
--	--	---	-------------------------------------	---	--------------------------------	--------------------------	--------------------------------

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●● Good (2/3) ●○ Possible (1/3) ○○○ Not recommended

MATERIAL	SPECIFICATION	GRP	21062-10
Alloyed and non-alloyed steels <small>Non-alloyed steels</small>	Rm < 450 N/mm ²	1a	●○
	Rm 450–700 N/mm ²	1b	○○
	Rm 700–900 N/mm ²	1c	○○
	Rm > 1200 N/mm ²	1d	○○
Stainless steels <small>Stainless steels</small>	Rm < 650 N/mm ²	2a	○○
	Rm 650–950 N/mm ²	2b	○○
	Rm > 950 N/mm ²	2c	○○
Hardened steels <small>Hardened steels</small>	44–56 HRC	3a	○○
	57–67 HRC	3b	○○
Exotic materials <small>Special alloys</small>	< 32 HRC	4a	○○
	> 32 HRC	4b	○○
Graphite <small>Industrial graphite</small>		5	●○
Cast iron <small>Grey / nodular cast iron</small>	< 32 HRC	6a	○○
	> 32 HRC	6b	○○
Titanium <small>Titanium alloys</small>	Rm < 600 N/mm ²	7a	●○
	600 < Rm N/mm ²	7b	●○
Nickel alloys <small>Inconel, Hastelloy</small>	Rm < 1000 N/mm ²	8a	○○
	Rm > 1000 N/mm ²	8b	○○
Copper, brass, bronze <small>Copper-based</small>	Rm < 850 N/mm ²	9a	●●●
	Rm > 850 N/mm ²	9b	●●●
Aluminum <small>Aluminum alloys</small>	Si < 0.5%	10a	●●○
	0.5% < Si < 5%	10b	●●○
	Si > 5%	10c	○○
Synthetic materials <small>Engineering plastics</small>	Thermoplastic	11a	●●●
	Thermoset	11b	●●●
Composite materials <small>Reinforced composites</small>	Glass fiber / GFK	12a	●○
	Carbon fiber / KFK	12b	●○
Precious metals <small>Gold, platinum, silver</small>	Gold	13a	●●●
	Platinum	13b	○○

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS	
D (0 / -0.01)	10 mm
d (h5)	10 mm
L	66 mm
l1	11 mm
l3	–
d3	–
R	–
e	–
Z	3
Chamfer K	0.1
w° collision	–

