FRAISE D'ÉBAUCHE MD E2 + EZI-ALPHA POUR MATÉRIAUX DIFFICILES · ROUGHING ENDMILL SC E2 + EZI-ALPHA FOR DIFFICULT MATERIALS · SCHAFT-SCHRUPPFRÄSER HM E2 + EZI-ALPHA FÜR HARTE WERKSTOFFE

TAKE IT EZI

SWISS MADE

21132A-12 Version 04.11.2026

E2
SUBMICRON GRAIN GRADE HIGH-SPEED MACHINING OF ABRASIVE MATERIALS

λ = 50°
Y = -12°
HELIX ANGLE 50° AND CUTTING ANGLE -12°

0.05–0.15
45°
CHAMFER AT 45° / HEIGHT 0.05 TO 0.15 MM

SIDE AND CENTER CUT

l1
1.5xD
CUTTING EDGE LENGTH 1.5XD

FITTING LENGTH STANDARD

IRREGULAR TOOTHING


MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility

CATEGORY	MATERIAL	SPECIFICATION	GRP	21132A-12
	Alloyed and non-alloyed steels Non-alloyed steels	Rm < 450 N/mm²	1a	○○○ 0/3
		Rm 450–700 N/mm²	1b	○○○ 0/3
		Rm 700–900 N/mm²	1c	●○○ 1/3
		Rm > 1200 N/mm²	1d	●●● 3/3
	Stainless steels Stainless steels	Rm < 650 N/mm²	2a	○○○ 0/3
		Rm 650–950 N/mm²	2b	●○○ 1/3
		Rm > 950 N/mm²	2c	●●○ 2/3
	Hardened steels Hardened steels	44–56 HRC	3a	●●● 3/3
		57–67 HRC	3b	●●○ 2/3
	Exotic materials Special alloys	< 32 HRC	4a	●●● 3/3
		> 32 HRC	4b	●●● 3/3
	Graphite Industrial graphite		5	○○○ 0/3
	Cast iron Grey / nodular cast iron	< 32 HRC	6a	●○○ 1/3
		> 32 HRC	6b	●○○ 1/3
	Titanium Titanium alloys	Rm < 600 N/mm²	7a	●○○ 1/3
		600 < Rm N/mm²	7b	●○○ 1/3
	Nickel alloys Inconel, Hastelloy	Rm < 1000 N/mm²	8a	●●● 3/3
		Rm > 1000 N/mm²	8b	●●● 3/3
	Copper, brass, bronze Copper-based	Rm < 850 N/mm²	9a	○○○ 0/3
		Rm > 850 N/mm²	9b	○○○ 0/3
	Aluminum Aluminum alloys	Si < 0.5%	10a	○○○ 0/3
		0.5% < Si < 5%	10b	○○○ 0/3
		Si > 5%	10c	○○○ 0/3
	Synthetic materials Engineering plastics	Thermoplastic	11a	○○○ 0/3
		Thermoset	11b	○○○ 0/3
	Composite materials Reinforced composites	Glass fiber / GFK	12a	○○○ 0/3
		Carbon fiber / KFK	12b	○○○ 0/3
	Precious metals Gold, platinum, silver	Gold	13a	○○○ 0/3
		Platinum	13b	○○○ 0/3

TECHNICAL DRAWING



21132

DIMENSIONS

NOMINAL DIMENSIONS	
D (h10)	12 mm
d (h6)	12 mm
L	83 mm
l1	18 mm
l3	–
d3	–
R	–
e	–
Z	4
Chamfer K	0.1
w° collision angle	-



E-SHOP / EZI CUT
eskenazi.ch/eshop/21132A-12

© 2026 Eskenazi SA — Carouge, Genève
All rights reserved