

|  |  |  |                                      |   |                                  |                           |  |
|--|--|--|--------------------------------------|---|----------------------------------|---------------------------|--|
| <b>E2</b><br>E2 HIGH PRECISION TOOL MATERIAL | $\lambda=32^{\circ}\text{-}38^{\circ}$<br>$\gamma=10^{\circ}$<br>ADJUSTABLE CUTTING ANGLES 32°-38° | $\phi < 6$ $\phi > 6$<br>90° 45°<br>CHAMFER $\phi < 6$<br>$\phi > 6$ 90° 45° | <br>DUAL DIRECTION HELICAL DRILL BIT | $l_1$<br>2.2xD<br>2.2XD DEPTH FOR TOOLS | <br>STANDARD TOOL WEAR INDICATOR | <br>ADJUSTABLE ANGLE ICON | $\lambda_2$<br>$\lambda_1$<br>VARIABLE HELIX DRILL BIT |
|--|--|--|--------------------------------------|---|----------------------------------|---------------------------|--|

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●● Good (2/3) ●○ Possible (1/3) ○○ Not recommended

| MATERIAL   | SPECIFICATION                | GRP | 21302A-4.5-6 |
|--|------------------------------|-----|--------------|
| <b>Alloyed and non-alloyed steels</b><br><small>Non-alloyed steels</small> | Rm < 450 N/mm <sup>2</sup>   | 1a  | ●●●          |
|  | Rm 450–700 N/mm <sup>2</sup> | 1b  | ●●●          |
|  | Rm 700–900 N/mm <sup>2</sup> | 1c  | ●●●          |
|  | Rm > 1200 N/mm <sup>2</sup>  | 1d  | ●●●          |
| <b>Stainless steels</b><br><small>Stainless steels</small>                 | Rm < 650 N/mm <sup>2</sup>   | 2a  | ●●●          |
|  | Rm 650–950 N/mm <sup>2</sup> | 2b  | ●●●          |
|  | Rm > 950 N/mm <sup>2</sup>   | 2c  | ●●●          |
| <b>Hardened steels</b><br><small>Hardened steels</small>                   | 44–56 HRC                    | 3a  | ○○○          |
|  | 57–67 HRC                    | 3b  | ○○○          |
| <b>Exotic materials</b><br><small>Special alloys</small>                   | < 32 HRC                     | 4a  | ●●○          |
|  | > 32 HRC                     | 4b  | ●●○          |
| <b>Graphite</b><br><small>Industrial graphite</small>                      |                              | 5   | ●●○          |
| <b>Cast iron</b><br><small>Grey / nodular cast iron</small>                | < 32 HRC                     | 6a  | ●●○          |
|  | > 32 HRC                     | 6b  | ●●○          |
| <b>Titanium</b><br><small>Titanium alloys</small>                          | Rm < 600 N/mm <sup>2</sup>   | 7a  | ●●●          |
|  | 600 < Rm N/mm <sup>2</sup>   | 7b  | ●●●          |
| <b>Nickel alloys</b><br><small>Inconel, Hastelloy</small>                  | Rm < 1000 N/mm <sup>2</sup>  | 8a  | ●●○          |
|  | Rm > 1000 N/mm <sup>2</sup>  | 8b  | ●●○          |
| <b>Copper, brass, bronze</b><br><small>Copper-based</small>                | Rm < 850 N/mm <sup>2</sup>   | 9a  | ●○○          |
|  | Rm > 850 N/mm <sup>2</sup>   | 9b  | ●○○          |
| <b>Aluminum</b><br><small>Aluminum alloys</small>                          | Si < 0.5%                    | 10a | ●○○          |
|  | 0.5% < Si < 5%               | 10b | ●○○          |
|  | Si > 5%                      | 10c | ●●○          |
| <b>Synthetic materials</b><br><small>Engineering plastics</small>          | Thermoplastic                | 11a | ○○○          |
|  | Thermoset                    | 11b | ○○○          |
| <b>Composite materials</b><br><small>Reinforced composites</small>         | Glass fiber / GFK            | 12a | ●●○          |
|  | Carbon fiber / KFK           | 12b | ●●○          |
| <b>Precious metals</b><br><small>Gold, platinum, silver</small>            | Gold                         | 13a | ●○○          |
|  | Platinum                     | 13b | ●○○          |

TECHNICAL DRAWING



DIMENSIONS

| NOMINAL DIMENSIONS |        |
|--------------------|--------|
| D (0 / -0.01)      | 4.5 mm |
| d (h5)             | 6 mm   |
| L                  | 57 mm  |
| l1                 | 11 mm  |
| l3                 | –      |
| d3                 | –      |
| R                  | –      |
| e                  | –      |
| Z                  | 3      |
| Chamfer K          | –      |
| w° collision       | 3.2°   |



E-SHOP / EZI CUT  
eskenazi.ch/eshop/21302A-4.5-6