

FRAISE-MULTI-USAGE-MD-E2+-EZI-ALPHA · MULTI-USE- ENDMILL-SC-E2+-EZI-ALPHA · FRÄSER-MULTI- VERWENDUNG-HM-E2+-EZI-ALPHA



SWISS MADE

21750A-90-4

Version 21.06.2026



MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

| MATERIAL | SPECIFICATION | GRP | 21750A-90-4 |
|---|------------------------------|-----|-------------|
| Alloyed and non-alloyed steels Non-alloyed steels | Rm < 450 N/mm ² | 1a | ●●● |
| | Rm 450-700 N/mm ² | 1b | ●●● |
| | Rm 700-900 N/mm ² | 1c | ●●● |
| | Rm > 1200 N/mm ² | 1d | ●●● |
| Stainless steels Stainless steels | Rm < 650 N/mm ² | 2a | ●●● |
| | Rm 650-950 N/mm ² | 2b | ●●● |
| | Rm > 950 N/mm ² | 2c | ●●● |
| Hardened steels Hardened steels | 44-56 HRC | 3a | ○○○ |
| | 57-67 HRC | 3b | ○○○ |
| Exotic materials Special alloys | < 32 HRC | 4a | ○○○ |
| | > 32 HRC | 4b | ○○○ |
| Graphite Industrial graphite | | 5 | ●●● |
| Cast iron Grey / nodular cast iron | < 32 HRC | 6a | ●●● |
| | > 32 HRC | 6b | ●●● |
| Titanium Titanium alloys | Rm < 600 N/mm ² | 7a | ●●● |
| | 600 < Rm N/mm ² | 7b | ●●● |
| Nickel alloys Inconel, Hastelloy | Rm < 1000 N/mm ² | 8a | ○○○ |
| | Rm > 1000 N/mm ² | 8b | ○○○ |
| Copper, brass, bronze Copper-based | Rm < 850 N/mm ² | 9a | ●●○ |
| | Rm > 850 N/mm ² | 9b | ●●○ |
| Aluminum Aluminum alloys | Si < 0.5% | 10a | ●●○ |
| | 0.5% < Si < 5% | 10b | ●●○ |
| | Si > 5% | 10c | ●●● |
| Synthetic materials Engineering plastics | Thermoplastic | 11a | ●○○ |
| | Thermoset | 11b | ●○○ |
| Composite materials Reinforced composites | Glass fiber / GFK | 12a | ●●● |
| | Carbon fiber / KFK | 12b | ●●● |
| Precious metals Gold, platinum, silver | Gold | 13a | ●●○ |
| | Platinum | 13b | ●●○ |

TECHNICAL DRAWING



DIMENSIONS

| NOMINAL DIMENSIONS | |
|--------------------|--------|
| D (0 / -0.01) | 4 mm |
| d (h5) | 4 mm |
| L | 50 mm |
| l1 | 8 mm |
| l3 | - |
| d3 | - |
| R | 0.4 mm |
| e | - |
| Z | 2 |
| Chamfer K | - |
| w° collision | - |



E-SHOP / EZI CUT
eskenazi.ch/eshop/21750A-90-4