

E2 E2 HIGH PRECISION TOOL MATERIAL	$\lambda=30^{\circ}\text{-}35^{\circ}$ $\gamma=8^{\circ}$ CUTTING ANGLES $730^{\circ}\text{-}35^{\circ}$ 78°	$0 \leq \phi < 6$ 90° 45° CHAMFER $\phi < 6$ $\phi > 6$ 90° 45°	 DUAL DIRECTION HELICAL DRILL BIT	$1.5 \times D$ 1.5XD DEPTH PRECISION TOOL	 SHORT LENGTH TOOL WEAR BARS	 ADJUSTABLE ANGLE ICON	$\lambda 2$ $\lambda 1$ VARIABLE HELIX DRILL BIT
--	--	--	--------------------------------------	--	---------------------------------	---------------------------	--

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●● Good (2/3) ●○ Possible (1/3) ○○○ Not recommended

MATERIAL	SPECIFICATION	GRP	22062-16
Alloyed and non-alloyed steels <small>Non-alloyed steels</small>	$R_m < 450 \text{ N/mm}^2$	1a	●○○
	$R_m 450\text{--}700 \text{ N/mm}^2$	1b	○○○
	$R_m 700\text{--}900 \text{ N/mm}^2$	1c	○○○
	$R_m > 1200 \text{ N/mm}^2$	1d	○○○
Stainless steels <small>Stainless steels</small>	$R_m < 650 \text{ N/mm}^2$	2a	○○○
	$R_m 650\text{--}950 \text{ N/mm}^2$	2b	○○○
	$R_m > 950 \text{ N/mm}^2$	2c	○○○
Hardened steels <small>Hardened steels</small>	44–56 HRC	3a	○○○
	57–67 HRC	3b	○○○
Exotic materials <small>Special alloys</small>	< 32 HRC	4a	○○○
	> 32 HRC	4b	○○○
Graphite <small>Industrial graphite</small>		5	●○○
Cast iron <small>Grey / nodular cast iron</small>	< 32 HRC	6a	○○○
	> 32 HRC	6b	○○○
Titanium <small>Titanium alloys</small>	$R_m < 600 \text{ N/mm}^2$	7a	●○○
	$600 < R_m \text{ N/mm}^2$	7b	●○○
Nickel alloys <small>Inconel, Hastelloy</small>	$R_m < 1000 \text{ N/mm}^2$	8a	○○○
	$R_m > 1000 \text{ N/mm}^2$	8b	○○○
Copper, brass, bronze <small>Copper-based</small>	$R_m < 850 \text{ N/mm}^2$	9a	●●●
	$R_m > 850 \text{ N/mm}^2$	9b	●●●
Aluminum <small>Aluminum alloys</small>	$Si < 0.5\%$	10a	●●○
	$0.5\% < Si < 5\%$	10b	●●○
	$Si > 5\%$	10c	○○○
Synthetic materials <small>Engineering plastics</small>	Thermoplastic	11a	●●●
	Thermoset	11b	●●●
Composite materials <small>Reinforced composites</small>	Glass fiber / GFK	12a	●○○
	Carbon fiber / KFK	12b	●○○
Precious metals <small>Gold, platinum, silver</small>	Gold	13a	●●●
	Platinum	13b	○○○

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS	
D (0 / -0.01)	16 mm
d (h5)	16 mm
L	82 mm
l1	16 mm
l3	–
d3	–
R	–
e	–
Z	3
Chamfer K	–
w° collision	–

