

FORET-2-LÈVRES-MD-E25UF-+-EZI-SMOOTH · 2-FLUTES-DRILL-SC-E2-5-UF-+-EZI-SMOOTH · ZWEI-LIPPEN-BOHRER-HM-E25-UF-+-EZI-SMOOTH



SWISS MADE

48401S-2.81

Version 07.05.2026

E25
UF

CARBIDE TOOL MATERIAL E25 UF

$\lambda = 20^\circ$

20° LAMBDA CUTTING ANGLE



90° RIGHT ANGLE DRILL BIT



TOOL LENGTH MEASUREMENT BARS

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

| MATERIAL | SPECIFICATION | GRP | 48401S-2.81 |
|---|------------------------------|-----|-------------|
| Alloyed and non-alloyed steels Non-alloyed steels | Rm < 450 N/mm ² | 1a | ●●● |
| | Rm 450–700 N/mm ² | 1b | ●●● |
| | Rm 700–900 N/mm ² | 1c | ●●● |
| | Rm > 1200 N/mm ² | 1d | ●●○ |
| Stainless steels Stainless steels | Rm < 650 N/mm ² | 2a | ●●● |
| | Rm 650–950 N/mm ² | 2b | ●●● |
| | Rm > 950 N/mm ² | 2c | ●●● |
| Hardened steels Hardened steels | 44–56 HRC | 3a | ●○○ |
| | 57–67 HRC | 3b | ○○○ |
| Exotic materials Special alloys | < 32 HRC | 4a | ●●○ |
| | > 32 HRC | 4b | ●●○ |
| Graphite Industrial graphite | | 5 | ●●● |
| Cast iron Grey / nodular cast iron | < 32 HRC | 6a | ●●● |
| | > 32 HRC | 6b | ●●● |
| Titanium Titanium alloys | Rm < 600 N/mm ² | 7a | ●●● |
| | 600 < Rm N/mm ² | 7b | ●●● |
| Nickel alloys Inconel, Hastelloy | Rm < 1000 N/mm ² | 8a | ●●○ |
| | Rm > 1000 N/mm ² | 8b | ●○○ |
| Copper, brass, bronze Copper-based | Rm < 850 N/mm ² | 9a | ●●● |
| | Rm > 850 N/mm ² | 9b | ●●● |
| Aluminum Aluminum alloys | Si < 0.5% | 10a | ●●● |
| | 0.5% < Si < 5% | 10b | ●●● |
| | Si > 5% | 10c | ●●○ |
| Synthetic materials Engineering plastics | Thermoplastic | 11a | ●●● |
| | Thermoset | 11b | ●●● |
| Composite materials Reinforced composites | Glass fiber / GFK | 12a | ●●● |
| | Carbon fiber / KFK | 12b | ●●● |
| Precious metals Gold, platinum, silver | Gold | 13a | ●●● |
| | Platinum | 13b | ●○○ |

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS

| | |
|---------------|---------|
| D (0 / -0.01) | 2.81 mm |
| d (h5) | 3 mm |
| L | 65 mm |
| l1 | 33.7 mm |
| l3 | 37.5 mm |
| d3 | – |
| R | – |
| e | – |
| Z | 2 |
| Chamfer K | – |
| w° collision | 0.1° |



E-SHOP / EZI CUT
eskenazi.ch/eshop/48401S-2.81

© 2026 Eskenazi SA — Carouge, Genève
All rights reserved