

MICRO-FORET-Z:2-AVEC-ARROSAGE-CENTRAL-MD-E25-UF-+-EZI-SMOOTH-D:2.90-D:3-L:63-L2:33-L3:35.5 · MICRO-FLUTES-DRILL-Z:2-WITH-THROUGH-COOLANT-CARBIDE-E25-UF-+-COATING-EZI-SMOOTH-D:2.90-D:3-L:63-L2:33-L3:35.5 · MIKRO-BOHRER-Z:2-MIT-INNENKÜHLUNG-HM-E25-UF-+-BESCHICHTUNG-EZI-SMOOTH-D:2.90-D:3-L:63-L2:33-L3:35.5



SWISS MADE

48480S-2.90

Version 07.05.2026

E2

E2 HIGH PRECISION TOOL MATERIAL

$\lambda = 20^\circ$

20° LAMBDA CUTTING ANGLE



90° RIGHT ANGLE DRILL BIT



TOOL LENGTH MEASUREMENT BARS



CENTRAL COOLANT DRILL BIT

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

| MATERIAL | SPECIFICATION | GRP | 48480S-2.90 |
|----------------------------------------------------------------------------|------------------------------|-----|-------------|
| Alloyed and non-alloyed steels <small>Non-alloyed steels</small> | Rm < 450 N/mm ² | 1a | ●●● |
| | Rm 450–700 N/mm ² | 1b | ●●● |
| | Rm 700–900 N/mm ² | 1c | ●●● |
| | Rm > 1200 N/mm ² | 1d | ●●● |
| Stainless steels <small>Stainless steels</small> | Rm < 650 N/mm ² | 2a | ●●● |
| | Rm 650–950 N/mm ² | 2b | ●●● |
| | Rm > 950 N/mm ² | 2c | ●●● |
| Hardened steels <small>Hardened steels</small> | 44–56 HRC | 3a | ●○○ |
| | 57–67 HRC | 3b | ○○○ |
| Exotic materials <small>Special alloys</small> | < 32 HRC | 4a | ●●● |
| | > 32 HRC | 4b | ●●● |
| Graphite <small>Industrial graphite</small> | | 5 | ●●● |
| Cast iron <small>Grey / nodular cast iron</small> | < 32 HRC | 6a | ●●● |
| | > 32 HRC | 6b | ●●● |
| Titanium <small>Titanium alloys</small> | Rm < 600 N/mm ² | 7a | ●●● |
| | 600 < Rm N/mm ² | 7b | ●●● |
| Nickel alloys <small>Inconel, Hastelloy</small> | Rm < 1000 N/mm ² | 8a | ●●○ |
| | Rm > 1000 N/mm ² | 8b | ●●○ |
| Copper, brass, bronze <small>Copper-based</small> | Rm < 850 N/mm ² | 9a | ●●● |
| | Rm > 850 N/mm ² | 9b | ●●● |
| Aluminum <small>Aluminum alloys</small> | Si < 0.5% | 10a | ●●● |
| | 0.5% < Si < 5% | 10b | ●●● |
| | Si > 5% | 10c | ●●● |
| Synthetic materials <small>Engineering plastics</small> | Thermoplastic | 11a | ●●● |
| | Thermoset | 11b | ●●● |
| Composite materials <small>Reinforced composites</small> | Glass fiber / GFK | 12a | ●●● |
| | Carbon fiber / KFK | 12b | ●●● |
| Precious metals <small>Gold, platinum, silver</small> | Gold | 13a | ●●● |
| | Platinum | 13b | ●●○ |

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS

| | |
|---------------|---------|
| D (0 / -0.01) | 2.9 mm |
| d (h5) | 3 mm |
| L | 57 mm |
| l1 | 21 mm |
| l3 | 35.5 mm |
| d3 | - |
| R | - |
| e | - |
| Z | 2 |
| Chamfer K | - |
| w° collision | - |



E-SHOP / EZI CUT
eskenazi.ch/eshop/484805-2.90